

**Automotive Electrical Wiring Harness Tapes**

EGI PRODUCT NUMBER	FORD SPECIFICATION	CHRYSLER SPECIFICATION	GM/DELPHI SPECIFICATION	EXTERIOR COLOR	DESCRIPTION	TYPICAL APPLICATION
<b>Coated Cloth Tapes</b>						
166	WSS-M3G177-B ES-XU5T-1A303-AA ES-AC3T-1A303-AA	166	M5207	Gray/Black	Polymeric Coated Cloth	Body Wire Harness Wrap Tape 85° C
264 NFR	264 NFR	MSCH71C	264NFR	Black	Polymeric Coated Cloth	Wire Harness Wrap Tape 85° C
268	ESB-M3G177-A ES-XU5T-1A303-AA ES-AC3T-1A303-AA	MSCH71A	M2399	Black	Polymeric Coated Cloth	Harness Wrap and Spot Tape Engine Compartment 105° C
277	ES-XU5T-1A303-AA-C01 ES-AC3T-1A303-AA	Approval to VW VW-C-1	277	Black	Polymeric Coated Cloth	Engine Compartment, High Temp Harness Wrap 125° C
281	ESB-M3G58-A	MSCH69 MS2629	9985514 9985159 9985144	Black	Polyethylene Coated Cloth	Moisture Resistant
398	398	398	M0537	Black	Vinyl Coated Cloth	Splice Covering and Insulation
518FR A	ESB-M3G71-B ES-XU5T-1A303-AA ES-AC3T-1A303-AA	518FR A	M4107	Black	Vinyl Coated Cloth	Splice Covering and Insulation
650	ES-AC3T-1A303-AA	MSCH71	M2399	Black	FR Wire Harness Tape	Harness Wrap and Spot Tape Engine Compartment 105° C
<b>Pressure Sensitive Tapes</b>						
ET935	ES-AC3T-1A303-AA	MS-12006	ET935	Black	Polyester	High Strength, High Abrasion, High Temp 150° C
ET950	ES-AC3T-1A303-AA	CS-11510	ET950	Black	Fleece	Squeak and Noise Reduction 105° C
ETN1000E	ES-XU5T-1A303-AA ES-AC3T-1A303-AA	MSDC13 CS-11510	M2147 M2148 M4037	Black	Pressure Sensitive Vinyl	Economical Harness Wrap Low VOC 85° C / 105° C
ET2100	ESB-M3G5-A	ET2100	TSC-1152 G VTE	Black	Pressure Sensitive Vinyl Splice Tape	Splice Covering
VTA090 FR	ES-AC3T-1A303-AA YPES 11-03-44	MSDC13B	VTA090 FR	Black	Pressure Sensitive Vinyl	Economical FR Harness Wrap 85° C
1700	ESB-M3G5-A	MSDC13B	M4037	Black and Colors	Pressure Sensitive Vinyl	Economical Harness Wrap 80° C
<b>Printed ID Tapes</b>						
EE12	ESB-M3G147-A	MSCH75	M0613	As specified by Customer	Cellulose	Printable ID / Code Tape
<b>Foil Tapes</b>						
3635	ES-F65B-14A121-AA	3635	M5115	Silver	Aluminum Foil Shielding Tape	EMI/RF Suppression
242C	ES-AC3T-1A303-AA	Pending	Pending	Silver	Foil-Laminated Polyester	Heat Reflective, High Temp 150° C
342C	ES-XU5T-1A303-AA ES-AC3T-1A303-AA	MS-11899	M2283	Aluminum / Silver	Aluminized Fiberglass Cloth Tape	Heat Reflective, High Temp 200° C

**Automotive Electrical Wiring Harness Tapes**

EGI PRODUCT NUMBER	FORD SPECIFICATION	CHRYSLER SPECIFICATION	GM/DELPHI SPECIFICATION	EXTERIOR COLOR	DESCRIPTION	TYPICAL APPLICATION
<b>Paper / Masking Tapes</b>						
P703 CP650	ESF-M3G25A	MSCH23	9985278/9985025 M0490	Tan	Pressure Sensitive Paper Tape	Bundling Tear Tape and Breakaway Tape
PB1	ESF-M3G25-A	MSCH28	9985278/9985025 M0490	Black	Pressure Sensitive Paper Tape	Bundling Tear Tape and Breakaway Tape
<b>Specialty Products</b>						
<b>Mastic Patches</b>						
DCC-1 Mastic Patch	ESB-M4G312-A WSK-M4G261	YPES-25-01-068-B1	DCC-1 Mastic	Black	Butyl Die-Cut Patch	Moisture Resistant Lightweight Applications Wire Splice Seal
EMS-II 60	EMS-II 60	EMS-II 60	M4091	Black	Moisture Sealant Pad	Insulation For Electrical Wire and Cables
<b>Foam Tapes</b>						
4314	ESB-M3G85-A Type II	MSCH612 MSCC211 MSAY301	M5133	Gray	Single coated Polyurethane Foam Low Density	Sound and Vibration Dampening / Air and Dust Seal
V710	WSB-M3G102-A	MSAY 511, A,B, C	GM6086M	Gray	Closed Cell Foam	Sound and Vibration Dampening / Air and Dust Seal
<b>Heat Shrink Tubing</b>						
Heat Shrink Tubing Single Wall	ESB-M99D56-A2	MSDB56	M2038	Black and Colors	Polyolefin Single Wall Tubing	Cover / Insulation of Wire Splices
Heat Shrink Tubing Dual Wall	ESF-M3L66-A	MSDB56	M2038	Black and Colors	Polyolefin Dual Wall Adhesive Lined Tubing	Insulate, Seal and Waterproof Harness Splices and Grommets

**Elliott Group International**  
**Elliott Tape, Inc. / EGI**  
**1882 Pond Run**  
**Auburn Hills, MI 48326**  
**Ph: 248-475-2000**  
**Fax: 248-475-5893**  
**Website: www.egitape.com**

**EGI / ElliottGroupInternational**  
**Industrial Tapes**

Description	Adhesion	Thickness	Applications
<b>Double Coated Tapes</b>			
Double Coated Cloth	Rubber: 29oz. - 45oz./in.	12.0 - 15.0 mil	General Mounting / Carpet Installation Convention Industry
Double Coated Crepe Paper	Rubber: 29oz. - 60oz./in.	4.0 - 6.0 mil	Joining Two Surfaces; Splicing, Textile / Printing Industry
Double Coated Polyester	Rubber, Acrylic: 90oz. - 130oz./in.	2.0 - 4.0 mil	Bond or Laminate Substrates
Transfer Adhesive	Rubber, Acrylic: 90oz./in.	2.0 - 5.0 mil	Permanent Bond of Plastic, Metal and Wood Substrates
<b>Cloth Tapes (Duct)</b>			
General Purpose / Duct Tapes Available in Black and Colors	Rubber: 45oz./in.	9.0 - 11.0 mil	General Industrial Use
Medium Grade Available in Black	Rubber: 45oz. - 65 oz./in.	10.0 mil	Muti-Purpose, Seaming, Strong Bond for Industrial Use
Premium Grade Available in Silver or Black	Rubber: 70oz./in.	12.0 mil	Seaming in HVAC Applications
Gaffers Tape Available in Black and Colors	Rubber: 50oz./in.	11.5 mil	Anchoring Wire/Cable Bundles
<b>Carton Sealing</b>			
Economy Grade Clear or Tan	Acrylic: 18oz./in.	1.6 mil	Light Weight Boxes
Production Grade Clear or Tan	Acrylic: 21oz./in.	2.0 mil	Medium Weight Boxes
Premium Grade	Acrylic: 25oz./in.	2.0 mil	Heavy Duty, High Holding Power
Tensitized Polypropylene Tape	Acrylic: 30oz./in.	2.0 - 4.0 mil	Strapping, Palletizing, Packaging
<b>Masking Tape</b>			
Medium Grade	Rubber: 40oz./in.	5.5 mil	Industrial use
Premium Grade	Rubber: 28oz./in.	6.8 mil	Heavy Grade With Low Adhesion For Ease of Removal
Performance High Temp	Rubber: 28oz./in.	7.7 mil	Versatile, Resistant to Solvents, Temp Resistant up to 325F.
Fine Line High Temp Masking	Rubber: 28oz. - 43oz./in.	5.5 to 6.3 mil	Conformable, Automotive Fine Line Separations, Paint Room Applications
Professional Painters Tape	Rubber: 19oz. - 33oz./in.	5.0 - 6.1 mil	Weather Resistant, Clean Removal for Sharp Trim Lines on Walls; Windows

**EGI / ElliottGroupInternational**  
**Industrial Tapes**

Description	Adhesion	Thickness	Applications
<b>Surface Protection</b>			
Low Density Polyethelene Film White, Clear	Acrylic: 2oz. - 33oz./in.	2.0 - 5.0 mil	Temporary Protection for Interior and Exterior Automotive Applications, Metal Fabrication, Appliance Protection
Transit Film White and Clear	Rubber: 11oz. - 17oz./in.	2.0 - 4.0 mil	Vehicle Exterior Painted Surface Protection From OEM to Dealer, UV Stable
Polypropylene Film Clear	Rubber: 9oz. - 24oz./in.	2.0 - 5.0 mil	Protection of Textured Interior parts, Screen Printed Products.
Paper Masking; Available in White and Brown	Latex: 6oz. - 28oz./in	4.0 - 6.0 mil	Paper Series for Surface Protection, Graphic arts, and Vinyl Sign Industry
Polyolefin Clear Film	Acrylic: 2oz./in.	3.0 mil	Window and Glass Protection, Clean Stain Free Removal after Extened Periods of Time, UV Stable
Low Density Poethelene Carpet Protection Film	Acrylic: 33oz. - 38oz./in.	3.0 mil	Carpet Protection for Automotive OEM to Dealer
<b>Double and Single Sided Foam Tapes</b>			
Polyurethane, Neoprene	Acrylic: Very high adhesion	.5mm - 2.3mm	Wide variety of foams available for all bonding applications
PVC	Acrylic: Very High Adhesion	1.6mm - 15.1mm	Sealing and Gasketing Applications
<b>Vinyls / Aisle Marking Tape</b>			
Vinyl Tape: Available in a variety of colors	Rubber: 22oz./in.	5.0 mil	General Purpose Marking Tape; Aisles, Shelving, Walls, Bundling
Vinyl Backed; Black, Yellow (BY), Black, White (BW), Red, White (RW)	Rubber: 18oz./in.	6.6 mil	Hazard or Warning Zone Marking on Floors or Walls
<b>Foil Tape</b>			
Dead Soft Aluminum Foil	Acrylic: 75oz./in.	3.8 mil	Sealing and Joining Duct Work HVAC Industry
<b>Polyimide "Kapton" Tape</b>			
Polyimide Film - Amber	Silicone: 25oz./in.	1 .0 - 2.0mil	Used on Coils, Capacitors and Harnesses
<b>Single Sided Films</b>			
Polyethylene; Blue, Clear, Yellow, Red, Orange, Black, White	Acrylic, Rubber: 25oz - 60oz./in.	6.5 - 8.0 mil	Abatement, Splicing, Greenhouse Repair, Abrasion Protection

**Elliott Group International**  
**Elliott Tape, Inc. / EGI**

**1882 Pond Run \* Auburn Hills, MI 48326 \* Ph: 248-475-2000 \* Fax: 248-475-5893**